

Description

Paracril CV is a particulate version of Paracril CLM using soluble PVC resin as a partitioning agent.

Packing

This product is commercialized in 55 Lb. Cartons/ 2,200 Lb. / Skid. The weight tolerance on cartons and skids is ± 2 percent.

Uses

Paracril CV offers good green strength and readily solvates in MEK. It is recommended for use adhesives, solvent cast seals and grommets.

Storage

Store in a dry and ventilated area where it will not be exposed to direct sunlight, extreme temperatures or sources of ignition.

Please consult Paracril CV "Material Safety Data Sheet" (MSDS) for more detailed handling and storage information.

Chemical properties

Property	Test method	Unit	Value
Total Volatile matter*	ASTMD 5668	(%)	1.0 max.
Total Ash*	ASTMD 5667	(%)	0.8 max.
Bound ACN*	INSA	(%)	33.7 – 36.7
Partitioning agent	INSA	(%)	10 - 12
Particle size passing 12 MM	INSA	(%)	99 min.
*Mooney viscosity ML 1+4 @ 100C	ASTMD 1646	MU	60 - 75

**Note polymer properties measured on the base polymer*

Physical properties

Property	Test method	Unit	Value
ML	ASTMD 2084	lb-in	4.6 – 7.6
MH	ASTMD 2084	lb-in	22.8 – 38.8
ts1	ASTMD 2084	Min.	2.5 – 4.8
t'50	ASTMD 2084	Min.	4.4 – 6.6
t'90	ASTMD 2084	Min.	11.2 – 21.8

July, 2016