

### Description

Paracril 45110 is a copolymer of butadiene and acrylonitrile, cold polymerized and non-staining stabilized.

### Packing

This product is commercialized in 25 Kg/Bale (55 Lb. /Bale) - 1,000 Kg/Skid - Net (2,200 Lb. /Skid.) rectangular bales individually wrapped in low melting point polyethylene film. Tolerance in all bale and packaging weights  $\pm 1$  percent.

### Uses

Paracril 45110 is designed with high BAN content for best fuel and oil resistance, high viscosity for improved green strength and increased oil content recipes, fast curing and light color. It is recommended for use in seals, O- Rings, packing, grommets, printing blankets and rolls.

### Storage

Store in a dry and ventilated area where it will not be exposed to direct sunlight, extreme temperatures or sources of ignition.

Please consult Paracril 45110 "Material Safety Data Sheet" (MSDS) for more detailed handling and storage information.

### Chemical properties

Property	Test method	Unit	Value
Total Volatile matter	ASTMD 5668	(%)	1.0 max.
Total Ash	ASTMD 5667	(%)	0.8 max.
Bound ACN	INSA	(%)	44 - 46
Specific Gravity	ASTMD 297	g/cc	1.01
Mooney viscosity ML 1+4 @ 100C	ASTMD 1646	MU	100 - 120

*\*Note ODR ranges will be established when enough lots have been produced to be statistically valid.*

July, 2016